

ISO 4126




Type 500




	ND	Set Pressure
BRASS	08 to 32	0,25 to 25 bar
CARBON STEEL	08 to 50	0,2 to 300 bar
STAINLESS STEEL	08 to 50	0,2 to 300 bar


TIGHT PLUG WITHOUT LEVER



UNTIGHT PLUG WITH LEVER




TIGHT PLUG WITH LEVER




Connection


CLAMP CONNECTION




INLET AND OUTLET CLAMP CONNECTION




SMS CONNECTION




INLET AND OUTLET SMS CONNECTION




SCREWED / THREADED




FLANGES / FLANGES



INLET AND OUTLET THREADED CONNECTION



FLANGES / THREADED



# Special design

**POLISHING**

**SPECIFIC LINED**

**PTFE  
INTERNAL  
PARTS**

## Order informations

MODEL	PLUG	CONNECTIONS	MATERIAL	ISO PN	OPTIONS	PN 10/25/40 100/250	DN CL 150/300 +NPT
5	1 TIGHT WITHOUT LEVER 5 UNTIGHT WITH LEVER 7 TIGHT WITH LEVER	0 SCREWED/THREADED BSP/NPT 1 FLANGE/FLANGE 2 FLANGE/THREADED BSP	A - CARBON STEEL	R - PN 40 1 - CLASS 150 3 - CLASS 300 RMP - PN 100	DISC [ T : PTFE JT : O'RING PFM JKA : O'RING KALREZ JEP : O'RING EPDM JN : O'RING NITRILE	DN 08 (1/4")	01 (1/4")
	1 TIGHT WITHOUT LEVER	0 SCREWED/THREADED BSP/NPT	A - CARBON STEEL	RHP - PN 250		*DN 10 (3/8")	02 (3/8")
	1 TIGHT WITHOUT LEVER 5 UNTIGHT WITH LEVER 7 TIGHT WITH LEVER	0 SCREWED/THREADED BSP/NPT 1 FLANGE/FLANGE 2 FLANGE/THREADED BSP/NPT 3 SCREWED/FLANGE	I- STAINLESS STEEL	R - PN 40 1 - CLASS 150 3 - CLASS 300 RMP - PN 100	TIGHTNESS [ PH : ALLOY C276 PH22 : HASTELLOY C22 TI : TITANE TA6V PE : SEAT PTFE + DISC PTFE/FFKM	*DN 15 (1/2")	03 (1/2")
	2 TIGHT WITHOUT LEVER 6 UNTIGHT WITH LEVER 8 TIGHT WITH LEVER	0 CLAMP/THREADED BSP/NPT 1 CLAMP/CLAMP 2 S.M.S./THREADED BSP/NPT 3 S.M.S./S.M.S.		R - PN 16		BT : LOW TEMPERATURE (GASKETS KEL'F)	*DN 20 (3/4")
	1 TIGHT WITHOUT LEVER	0 SCREWED/THREADED BSP/NPT	I- STAINLESS STEEL	RHP - PN 250	HT : HIGH TEMPERATURE (GASKETS GRAPHITE)	*DN 25 (1")	10 (1")
					ST : NOZZLE AND DISC STELLITED	DN 32 (1.1/4")	11 (1.1/4")
					DN 40 (1.1/2")	13 (1.1/2")	
					DN 50 (2")	20 (2")	